


# MATERIALS TRANSPORTATION COMPANY<sup>™</sup>





MTC engineers, designs and manufactures the most comprehensive line of battery handling equipment available in the industry today. Ranging from a single stacking Power Charger to the fully automated Intell-A-Changer, MTC can provide complete design assistance to create a customized solution for any application. We are focused on providing sustainable systems using the latest technology to enhance your battery room. Please review our catalog and connect with us through our website or a regional manager near you for more information on an MTC custom Battery Room Solution.

Greg Camp Vice President Sales and Marketing





# **ALPHABETICAL INDEX**

The state of the s
AC Power Systems 10
Attach-A-Puller 6
Attach-A-Puller Accessories 6
В
Battery Charge Monitor 14
Battery Cleaning Kits 15
Battery Rollers 13
Battery Service Station 5
Battery Spill Response Kit 12
Battery Station with Acid-Resistant Interlay 11
Battery Station with Rollers 4
Battery Transporter 8
Battery Wash Cabinets 14
Battery Wash Racks 14
C
Cell Filler 13
Charger Cable Retractor 12
E
EZ-Puller 9
F
Floor Mounted Charger Support 12
Floor Track 10,11
Fork Attachment 12
Н
Handling Beams 12
Heavy Duty Roller Tray 13
High Frequency Charger Stands 9
Hoists 11

L
Liquid Neutralizing Conditioner 14
N
Neutralizing Acid Absorber 12
O
Overhead Removal Systems 10, 11
P
Personal Safety Kit 13
R
"R" Dimension Information 4
Remote Charge Indicator 14
S
Shower & Eyewash 13

#### W

Slide Strips 13

Walk-A-Puller 7
Wall Mounted Charger Support 12
Water De-Ionizer Filter Kits 15
Water Delivery Kits 15

Stainless Steel Drip Pans 5, 11

# **BATTERY STATIONS WITH ROLLERS**

Model Approx. Wt.

Two-Compartment Battery St	ation with Rollers
RS-12-2	225 lbs.
RS-15-2	260 lbs.
RS-18-2	310 lbs.
RS-21-2	325 lbs.
RS-24-2	355 lbs.
RS-24-2-45**	394 lbs.
RS-27-2	385 lbs.
RS-30-2	440 lbs.
RS-34-2	480 lbs.

Three-Compartment Battery Station	on with Rollers
RS-12-3	280 lbs.
RS-15-3	350 lbs.
RS-18-3	425 lbs.
RS-21-3	485 lbs.
RS-24-3	515 lbs.
RS-24-3-45**	572 lbs.
RS-27-3	590 lbs.
RS-30-3	665 lbs.
RS-34-3	800 lbs.

Specify "R" Dimension.

#### "R" Dimension Information

The "R" dimension is measured from the floor to the top of the rollers in the battery station. This dimension is required on all Roller Stations and Battery Service Stations. The minimum "R" dimension on RS and B-SS equipment is 5.5".



(RS) Battery Station with Rollers



<sup>\*\* &</sup>quot;-45" on Model Number indicates 45" depth. For Battery Cable Retractor see Page 12.

Model	Approx. Wt
-------	------------

Stainless Steel Drip Pans for Two Com	partments
SSDP-RS12-2-SL	15 lbs.
SSDP-RS15-2-SL	19 lbs.
SSDP-RS18-2-SL	25 lbs.
SSDP-RS21-2-SL	32 lbs.
SSDP-RS24-2-SL	54 lbs.
SSDP-RS24-2-SL-45	49 lbs.
SSDP-RS27-2-SL	52 lbs.
SSDP-RS30-2-SL	56 lbs.
SSDP-RS34-2-SL	61 lbs.

Stainless Steel Drip Pans for Two	Compartments
SSDP-RS12-3-SL	24 lbs.
SSDP-RS15-3-SL	29 lbs.
SSDP-RS18-3-SL	35 lbs.
SSDP-RS21-3-SL	42 lbs.
SSDP-RS24-3-SL	56 lbs.
SSDP-RS24-3-SL-45	61 lbs.
SSDP-RS27-3-SL	61 lbs.
SSDP-RS30-3-SL	65 lbs.
SSDP-RS34-3-SL	69 lbs.

Battery Service Station	
B-SS-15	86 lbs.
B-SS-21	140 lbs.
Specify "R" Dimension	



(B-SS) Battery Service Station

## SIDE REMOVAL SYSTEMS

### **PORTABLE BATTERY CHANGERS**

Model Approx. Wt.

Attach-A-Puller	
ABP-24-V(M)-24	670 lbs.
ABP-32-V(M)-24	768 lbs.
ABP-40-V(M)-24	770 lbs.
ABP-24-V(M)-44-24	815 lbs.
ABP-32-V(M)-44-24	893 lbs.
ABP-40-V(M)-44-24	915 lbs

V=Vacuum M=Magnet (Available 24 Volt models only)(-24) indicates 24-Volt Model. For 12-Volt Models, change (-24) to (-12). For special applications, consult factory.

#### Attach-A-Puller Accessory

ABP-FP9 69 lbs.

Attach-A-Puller Accessory

Attach-A-Puller Fork Pockets Kit (9" fork width); includes hardware and installation instructions. For use on pallet truck only.







Model	Approx. Wt.
Walk-A-Pu	ller
WBP-40-V(M)-44	3250 lbs.
WBP-40-V(M)-44-Side	3255 lbs.
V=Vacuum M=Magnet	

## SIDE REMOVAL SYSTEMS

### **PORTABLE BATTERY CHANGERS**

Model Approx. Wt.

Battery Transporter with Med	thanical Loader
BT-16-ML	435 lbs.
BT-24-ML	530 lbs.
BT-30-ML	650 lbs.

#### Available Options:

- Extension Kit (-EK)
- Track Mounted (-TM)
- Use Track-1-.5x1
- Low Profile (-LP)

#### **Battery Transporter (Powered)**

BT-24-ML-P-DC 700 lbs
Powered up-down/ in-out only

#### Available Options:

- Extension Kit (-EK)
- Track Mounted (-TM)
- Use Track-1-.5x1
- Low Profile (-LP)







(EZP) EZ-Puller



Model Approx. Wt.

High Fraguency Charger Stands	
High Frequency Charger Stands	
CSHF-72x10-C High frequency charger stand, single 72" x 10" w/cable retractor bracket	48 lbs.
CSHF-72x10-2C High frequency charger stand, double 72" x 10" w/cable retractor brackets	48 lbs.
CSHF-72x17-C High frequency charger stand, single 72" x 17" w/cable retractor bracket	48 lbs.
CSHF-72x17-2C High frequency charger stand, double 72" x 17" w/cable retractor brackets	48 lbs.
CSHF-72x20-C High frequency charger stand, single 72" x 20" w/cable retractor bracket	48 lbs.
CSHF-72x20-2C High frequency charger stand, double 72" x 20" w/cable retractor brackets	48 lbs.

ole retractor brackets

pockets

\*Note: Cable Retractor not included. CSHF weight includes box for shipping.

EZ-Puller	
EZP-24	510 lbs.
Pallet truck mounted, manual hand crank battery extractor, 24"	
EZP-24-FP Pallet truck mounted, manual hand crank battery e.	540 lbs. xtractor, 24", with fork

# **OVERHEAD REMOVAL SYSTEMS**

Model	Approx. Wt.
Powered 2-Ton Traveling* <sup>‡</sup>	
HTG2-16	1540 lbs.
HTG2-18	1605 lbs.
HTG2-20	1670 lbs.
Powered 3-Ton Traveling**	
HTG3-16	1540 lbs.
HTG3-18	1775 lbs.
HTG3-20	1860 lbs.
*Track required, see below.	
Floor Track – HTG	
*Track-262X2 Flat bar for HTG (Track two sides)	per ft.
*Track-162X2 Flat bar for HTG-T1 (Track one side only)	per ft.
AC Power Systems	
BCRL-30-14-4	49 lbs.
Cable reel, 30 foot 14 AWG / 4 cond. S.O. Cable	
BCRL-50-14-4	77 lbs.
Cable reel, 50 foot 14 AWG / 4 cond. S.O. Cable	
BCRL-70-14-4	105 lbs.

Cable reel, 50 foot 14 AWG / 4 cond. S.O. Cable	
BCRL-70-14-4	105 lbs.
Cable reel, 70 foot 14 AWG / 4 cond. S.O. Cable	
BCRL-30-SWIVEL	1 lb.
Swivel base for 30 foot battery cable reel	
BCRL-50-SWIVEL	5 lbs.
Swivel base for 50 foot battery cable reel	

Swivel base for 70 foot battery cable reel

**BCRL-70-SWIVEL** 

Hoists-Motorized Trolley		
NERM-020C-L	218 lbs.	
2 ton ECH motorized trolley, 40 fpm, 10' lift, 7 fpm,		
pendant priced separately, includes canvas chain cont	ainer.	
NERM-030C-L 340 lbs.		
3 ton ECH motorized trolley, 40 fpm, 10' lift, 17 fpm,		
pendant priced separately, includes canvas chain cont	ainer.	
NER-6B	4.1 lbs.	
Pendant for motorized trolley, 6 button.		

Approx. Wt.

4.6 lbs.

3.2 lbs.

Model

NER-8B

NER-4B

5 lbs.

Pendant for motorized trolley, 8 button.

Hoists-Push Trolley	
NERP-020C	176 lbs.
2 ton ECH push trolley, 10' lift, 7 fpm,	
pendant priced separately, includes canvas chain conta	ainer.
NERP-030C	291 lbs.
3 ton ECH push trolley, 10' lift, 17 fpm,	
pendant priced separately, includes canvas chain conta	ainer.
NER-2B	3.1 lbs.
Pendant for push trolley, 2 button.	

Pendant for push trolley, 4 button.

Prices are for standard 240/480V 3 phase. Other voltages available. Please specify required voltage when ordering.





<sup>‡</sup> Gantry Cranes, 10' standard under beam clearance, model # indicates horizontal clearance.

		1.1.
	Non-Powered 2-Ton Traveling*	:
TG2-10		855 lbs.
TG2-12		980 lbs.
TG2-14		1030 lbs.
TG2-16		1190 lbs.
TG2-18		1255 lbs.
TG2-20		1320 lbs.

Model

	Non-Powered 3-Ton Traveling* <sup>‡</sup>
TG3-10	930 lbs.
TG3-12	980 lbs.
TG3-14	1130 lbs.
TG3-16	1310 lbs.
TG3-18	1370 lbs.
	Floor Track – TG

\*Track-1-Angle per ft. Angle with tabs, required for TG models.

Battery Station with Acid-R	esistant Interlay
HS-30	245 lbs.
HS-42	330 lbs.
HS-42-LR	330 lbs.
HS-60	410 lbs.
HS-60-LR	410 lbs.
HS-72	485 lbs.
HS-72-LR	485 lbs.
HS-84	600 lbs.
HS-84-LR	600 lbs.
HS-100	660 lbs.
HS-100-LR	660 lbs.
HS-120	745 lbs.
HS-120-LR	745 lbs.
HS-144	925 lbs.
HS-144-LR	925 lbs.
I Dividiant and after Divide Handon and form	

-LR indicates Left to Right Hardwood, for use with batteries 13" or less.

N /	-		
-1\/	00	$\Theta$	

Approx. Wt.

Model	Approx. Wt.	
Non-Powered 2-Ton Portable <sup>†</sup>		
PG2-10	855 lbs.	
PG2-12	950 lbs.	
PG2-14	1030 lbs.	
Hoist		
NERP-020C**	176 lbs.	
2 ton electric chain hoist with plain trolle	ey and chain container	
NER-2B	3.1 lbs.	

Pendant for push trolley, 2 button.

Non-Powered 3-Ton Po	ortable <sup>‡</sup>
PG3-10	930 lbs.
PG3-12	980 lbs.
PG3-14	1130 lbs.
Hoist	
NERP-030C**	291 lbs.
3 ton electric chain hoist with plain trolley and c	hain container.
NER-2B	3.1 lbs.
Pendant for push trolley, 2 button.	

\*\*For use with PG and TG crane models only.

Stainless Steel Drip Pans for HS-Ba	ttery Stations
SSDP-HS-30	21 lbs.
SSD-HS-42	25 lbs.
SSDP-HS-60	35 lbs.
SSDP-HS-72	42 lbs.
SSDP-HS-84	49 lbs.
SSDP-HS-100	56 lbs.
SSDP-HS-120	70 lbs.
SSDP-HS-144	84 lbs.



<sup>#</sup> Gantry Cranes, 10' standard under beam clearance, model # indicates horizontal clearance.

# **ACCESSORIES**

Model	Approx. Wt.	
Charger Cable Retractor		
BCR-58H	7 lbs.	
BCR-OH-HD	7 lbs.	
Floor Mounted Charger Support		
CSF-24	70 lbs.	
CSF-36	85 lbs.	
CSF-48	140 lbs.	
CSF-72	170 lbs.	
Wall Mounted Charger Support		
CSW-2	30 lbs.	
CSW-BCR-58	0.5 lbs.	
Fork Attachment		
FA-6000	25 lbs.	
Handling Beams (Non-Conduction	ve)	
HB-4000-PL	59 lbs.	
Handling beam, 4000 lbs. with posi-latch safety design		
HB-6000-PL	66 lbs.	
Handling beam, 6000 lbs. with posi-latch safety design		
Battery Spill Response Kit		
BERK-S	35 lbs.	
Battery Spill Response Kit (small)		
BERK-L Battery Spill Response Kit (large)	60 lbs.	
	EO lbs	
NAA-3048 Neutralizing acid absorber (bulk 48 lbs.)	50 lbs.	
NAA-30210	225 lbs.	
Neutralizing acid absorber (bulk 210 lbs.)	223 103.	
NAA-30500	550 lbs.	
Neutralizing acid absorber (bulk 500 lbs.)		





BERK-S







SK-1





Model	Approx. Wt.
Truck Conversion Options	
Heavy Duty Roller Tray	
HRT-2*	12 lbs.
HRT-3*	18 lbs.
* Specify compartment length and width.	
Slide Strips	
B-UPS-*	
B-UPS-R-**	
*Specify overall length. (-XX)	
**"-R" indicates Lead-in Roller.	
Battery Rollers	
BR-HD	1 lb.
Personal Safety Kit	
SK-1	5 lbs.
BCK-WCA	5 lbs.
Shower & Eyewash	
SEW-303	62 lbs.
Shower eyewash, floor mount, yellow bowl G1902P	
EW-304	6 lbs.
Eyewash, bowl, less shower G1814P	
PEW-700	19 lbs.
Portable eyewash, wall mount G1540	
Cell Filler & Water Carts	
CF-X	2 lbs.
BWC-CRT-12V	27 lbs.
Water cart, 10 gallon, 12VDC, use w/ CF-X	
BWC-CRT-T10G	60 lbs.
Water cart, 10 gallon, use w/ CF-X	

## **ACCESSORIES**

Model Approx. Wt. **Battery Wash Cabinets** WCA-SS 1200 lbs. WCA-SS-PR\* 1300 lbs. WCA-SS-SB\*\* 1300 lbs. WCA-OH-SS\*\*\* 1950 lbs. WCA-OH-SS-SB 1950 lbs. WCA-1C-SS\*\*\*\* 1950 lbs. 1950 lbs. WCA-1C-SS-SB



<sup>\*\*</sup> SB – Bottom scrub brush and powered rollers

<sup>\*\*\*\* 1</sup>C - Infeed conveyor model (PCHE systems)

Battery Wash Ra	acks
WRR-SS	650 lbs.
WR-OH-SS	625 lbs.

#### WR-SUMP-ASSY\*

<sup>\*</sup> Sump assembly is required for wash racks being used with a recirculating water system

being used with	n a recirculating water system.			
	Recirculating Water Syst	em		
H2O-150S	S-NOS	630 lbs.		
H2O-300SS-NOS		785 lbs.		
Liquid Neutralizing Conditioner (for H2O Units)				
LNC	1 gallon	6 lbs.		
LNC-5	5 gallon pail	51 lbs.		
LNC-55	55 gallon drum	525 lbs.		
Battery Charge Monitor				
RCI-1000		1 lb.		
Remote charge	indicator, displays charger on, char	ge 80%, charge		
complete and I	pattery cooled			
RCI-1000-E		1 lb.		







SYSTEMS SERVI

Remote charge indicator w/ equalizer button

<sup>\*\*\*</sup> OH – Overhead loading (HTG models)





BCK-10

Water Delivery Kits **INJ-HCT** 64 lbs. 20 gallon water cart, AC powered pump, 110V. For use with Philadelphia Scientific water injector strings or watering gun. 6.5 lbs. **INJ-DF** Direct fill hose assembly INJ-P12-SPEC\* Fully assembled water injector system. 12 cell battery type, includes connector. Ready to install INJ-P18-SPEC\* Fully assembled water injector system. 18 cell battery type, includes connector. Ready to install. INJ-P24-SPEC\* Fully assembled water injector system. 24 cell battery type, includes connector. Ready to install. **INJ-ACC-BWM** 1.5 oz. Battery watering monitor \* Must specify battery make, model, cable length and position. INJ-T10M 60 lbs. Bladder tank mini, 10 gallon, mobile INJ-Mini 32 lbs. Hydro cart mini, 8 gallon, mobile, AC powered PS-300 27 lbs. Water de-ionizer system PS-600 14 lbs. Water de-ionizer filter, 600 gallon (replacement filter) Battery Cleaning Kits BCK-10 10 lbs. Kit includes chemicals, gloves, brushes and goggles 10 lbs. BCWI-2500-4Q Battery cleaner with indicator, 4 quart case BCWI-2500-12Q 30 lbs. Battery cleaner with indicator, 12 quart case 45 lbs. BCWI-2500-5G Battery cleaner with indicator, 5 gallon pail 525 lbs. BCWI-2500-55G Battery cleaner with indicator, 55 gallon drum

Model

# **CESOLUTIONS**

Approx. Wt.



# MATERIALS TRANSPORTATION COMPANY<sup>™</sup>



### An Employee Owned Company

P.O. Box 1358 Temple, Texas 76503 USA Phone (254) 298-2900 • Fax (254) 771-0287 U.S. (800) 433-3110

email: battery@mtcworldwide.com

mtcworldwide.com

© 2014 Materials Transportation Company All Rights Reserved BHSC-0214